

### **TECHNICAL DATA SHEET**

RAXTAR of the Netherlands is a privately owned organization that provides world class vertical access solutions: construction hoists for passengers & materials, material hoists, transport platforms and industrial lifts. RAXTAR builds on innovation & technology to deliver unequalled operational reliability at the lowest total cost of ownership (TCO) in the market. RAXTAR is a synonym for meeting the highest quality- and safety standards.



#### **RX3645SF Passenger & Material Hoist**

#### **TECHNICAL DATA\***

CAPACITY

Payload : 3600 kg 8000 lb

Lifting speed : 0 - 75 - 92 m/min 0 - 250 - 300 ft/min

Counter weight : No No Maximum lifting height : 400 m 1320'

**DIMENSIONS & WEIGHT** 

Hoist car internal dimensions (I x w x h) : 4.42 x 1.52 x 2.60 m 14′ 6″ x 5′x 8′ 6½″ Ground enclosure (I x w x h) : 4.81 x 2.69 x 2.94 m 15′ 9″ x 9′ 10″ x 9′ 8″

Length mast section: 1.51 m4'11"Weight mast section, single rack: 120 kg265 lbWeight mast section, double rack: 150 kg330 lb

**ELECTRICAL DATA** 

Motor : 3x 22 kW 3x 22 kW Power supply : 400 V - 50 hz, 3p 460 V - 60 hz, 3p 110 V / 230 V power on platform : Standard, included Overload device : Standard, included Standard, included

Automatic lubrication : Optional Optional

**HOIST CONTROLS** 

Controls : Frequency control / SNL / PLC Frequency control / SNL / PLC

User interface : Joystick / touch panel Joystick / touch panel

Blue tooth communication : Optional Optional

Manual controls / erection controls : Standard, included
Drop test controls : Standard, included Standard, included

Programmable landings: OptionalOptionalHoist calling system: OptionalOptionalRX Control, internet management control: OptionalOptional

<u>GENERAL</u>

Finishing cabin / ground enclosure : Galvanized / powder coated Galvanized / powder coated

Company logo and color : Optional Optional

Ground enclosure : Standard, included Standard, included

C-door : Optional Optional

Cable trolley system : Standard, included Standard, included


Erection jib : Optional Optional


Norms & regulations : Machine Directive (EN12159+A1) / Machine Directive (EN12159+A1) /

A10.4:2007 (USA) A10.4:2007 (USA)




## **RX3645SF Passenger & Material Hoist**






1645mm 5'-4 3/4'

Top view





De Run 4455, NL-5503 LS Veldhoven The Netherlands T +31(0)88 369 0000


E info@raxtar.com


I www.raxtar.com

\*Data based on a standard configuration
This information is subject to change without prior notice.
Version: 1-2012





# RX3645SFT Passenger & Material Hoist (twin configuration)





Top view





De Run 4455, NL-5503 LS Veldhoven The Netherlands T +31(0)88 369 0000

E info@raxtar.com

I www.raxtar.com

\*Data based on a standard configuration

This information is subject to change without prior notice.

Version: 1-2012